


### Interfilm Type OM Matte, Overlamine Film



## Product Features

**DESCRIPTION:** Co-extruded polypropylene film with a matte finish layer on one side and a high gloss layer for lamination on the other. It is corona treated on both sides for ink and adhesive adhesion. This material is NOT heat sealable.

### FEATURES:

- Matte Surface on One Side
- High Gloss One Side
- Reduces Reflection; Making Printing More Readable
- Good Machineability
- Excellent Dimensional Stability

### APPLICATIONS:

- Lamination by Adhesive or Extrusion Process
- Overlamination of Labels, Brochures, Leaflets, Paper and Catalogues

Property		Value		Unit	Test Method
<b>Physical Properties</b>					
Thickness		60	120	gauge	
Yield		51,500	25,500	in <sup>2</sup> /lb	
Tensile Strength	MD	19,880	16,000	PSI	ASTM D 882
	TD	42,600	38,000		
Elongation	MD	135	200	%	ASTM D 882
	TD	50	50		
COF	Matte	0.25	0.50		ASTM D 1894
Surface Tension	Front	38		PSI	ASTM D 882
	Back	38			
<b>Optical Properties</b>					
Haze		70	45	%	ASTM D 1003
Gloss	Matte	20	20	%	ASTM D 2457
	High Gloss	60	100		

\* All values +/- 10%

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Interfilm Holdings, Inc., and Interfilm Holdings, Inc., makes no warranty of results to be obtained. Users should make their own tests to determine the suitability of these products for their own particular purposes. However, because of the numerous factors affecting results, Interfilm Holdings, Inc., MAKES NO REPRESENTATIONS OF ANY WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, OR ANY OTHER MATTER WITH RESPECT TO THE MATERIAL OTHER THAN THAT THE MATERIAL CONFORMS TO ITS APPLICABLE CURRENT STANDARD SPECIFICATIONS. Statements herein, therefore, should not be construed as representations or warranties. THE RESPONSIBILITY OF INTERFILM HOLDINGS, INC. FOR CLAIMS ARISING OUT OF BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY OR OTHERWISE IS LIMITED TO THE PURCHASE PRICE OF THE MATERIAL.

## Standard Roll Sizes

Available Core Sizes →		3"	3"	3" or 6"	6"	6"
Approximate Roll OD →		9.50	11.00	13.00	18.75	22.50
Roll Weight Multiplier →		2.00	2.82	3.90	7.80	10.35
Gauge	Microns	Approximate Roll Lengths				
48	12	10,125	15,188	20,250	40,500	60,750
60	15	8,100	12,150	16,200	32,400	48,600
70	18	6,750	10,125	13,500	27,000	40,500
75	19	6,383	9,575	12,767	25,533	38,300
80	20	6,067	9,100	12,133	24,267	36,400
90	22	5,500	8,250	11,000	22,000	33,000
100	25	4,933	7,400	9,867	19,733	29,600
120	30	4,017	6,025	8,033	16,067	24,100
140	35	3,500	5,250	7,000	14,000	21,000
160	40	3,050	4,575	6,100	12,200	18,300
200	50	2,433	3,650	4,867	9,733	14,600
210	52	2,317	3,475	4,633	9,267	13,900
240	60	2,033	3,050	4,067	8,133	12,200

\*Non-standard roll lengths/OD's are available on special request.

Roll Weight Estimator = (width of roll in inches) X (Roll Weight Multiplier at desired OD)

### Available Widths

- Most films are available in roll widths from ¼ inch to 80 inches

### Minimum Order Quantities

- Minimum order quantity is 500 lbs. Freight will be prepaid and added to invoice.
- Production orders less than 500 lbs. will incur a less than minimum order fee.
- Orders greater than 1000 lbs. are shipped freight paid.

### Plant Locations

Nationwide service through four plants locations.

